

01-20-00 A

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

UTILITY PATENT APPLICATION TRANSMITTAL  
UNDER 37 CFR 1.53(b)

Address to:  Assistant Commissioner for Patents  Box Patent Application  Washington, DC 20231	Attorney Docket No.	AM9-99-0226
	Inventor(s)	Agrawal et al.
	Express Mail Label No.	EL535054229US
	Total Pages	28

Title of Application:

**SYSTEM AND ARCHITECTURE FOR PRIVACY-PRESERVING DATA MINING**

Transmitted with the patent application are the following:

- 1 Page(s) Transmittal form (plus one copy)
- 20 Page(s) Specification, claims, abstract
- 3 Page(s) Drawings
- 2 Page(s) Declaration and Power of Attorney
- 1 Page(s) Recordation Form Cover Sheet
- 1 Page(s) Assignment of the Invention to International Business Machines Corporation

jc678 U.S. PTO  
09/487191  
01/19/00

This application is a: ☐ Continuation ☐ Divisional ☐ Continuation-in-Part of prior application Serial No. \_\_\_\_\_

**Fee Calculation**

	Claims Filed		Extra	Rate	Fees
Basic Fee					\$690.00
Total Claims	23	- 20 =	3	× \$18.00	54.00
Independent Claims	4	- 3 =	1	× \$78.00	78.00
Multiple Dependent Claim				+ \$260.00	
				Assignment	\$ 40.00
				<b>TOTAL</b>	<b>\$862.00</b>

The Commissioner is hereby authorized to credit overpayments or charge fees required under 37 CFR 1.16 or 1.17 to Deposit Account 09-0441.

**EXPRESS MAIL CERTIFICATE**

I hereby certify that the above paper/fee is being deposited with the United States Postal Service "Express Mail Post Office to Addressee" service under 37 CFR 1.10 on the date indicated below and is addressed to the Assistant Commissioner for Patents, Washington, DC 20231

Date of Deposit: January 19, 2000  
Person mailing paper/fee: Jeanne Gahagan

Signature: [Signature]

Respectfully submitted,

[Signature]  
John L. Rogitz (#33,549)  
Attorney for Applicant(s)  
Telephone (619) 338-8075  
Rogitz & Associates  
750 B Street, Suite 3120  
San Diego, California 92101

# SYSTEM AND ARCHITECTURE FOR PRIVACY-PRESERVING DATA MINING

## BACKGROUND OF THE INVENTION

### 1. Field of the Invention

The present invention relates to mining data from Internet users while preserving the privacy of the users.

### 2. Description of the Related Art

5 The explosive progress in computer networking, data storage, and processor speed has led to the creation of very large data bases that record enormous amounts of transactional information, including Web-based transactional information. Data mining techniques can then be used to discover valuable, non-obvious information from large databases.

Not surprisingly, many Web users do not wish to have every detail of every transaction recorded. Instead, many Web users prefer to maintain considerable privacy. Accordingly, a Web user might choose not to give certain information during a transaction, such as income, age, number of children, and so on.

15 It happens, however, that data mining of Web user information is not only useful to, e.g., marketing companies, but it is also useful in better serving Web users. For instance, data mining might reveal that people of a certain age in a certain income bracket might prefer particular types of vehicles, and generally not prefer other types. Consequently, by knowing the age and income bracket of a particular user, an automobile sales Web page can be presented that lists the likely vehicles of choice to the user, before other types of vehicles, thereby making the shopping

experience more relevant and efficient for the user. Indeed, with the above in mind it will be appreciated that data mining makes possible the filtering of data to weed out unwanted information, as well as improving search results with less effort. Nonetheless, data mining used to improve Web service to a user requires information that the user might not want to share.

5 As recognized herein, the primary task of data mining is the development of models about aggregated data. Accordingly, the present invention understands that it is possible to develop accurate models without access to precise information in individual data records. Surveys of Web users indicate that the majority of users, while expressing concerns about privacy, would willingly divulge useful information about themselves if privacy measures were implemented, thereby facilitating the gathering of data and mining of useful information. The present invention has carefully considered the above considerations and has addressed the noted problems.

### SUMMARY OF THE INVENTION

10 The invention is a general purpose computer programmed according to the inventive steps herein to mine data from users of the Internet while preserving their privacy. The invention can also be embodied as an article of manufacture - a machine component - that is used by a digital processing apparatus and which tangibly embodies a program of instructions that are executable by the digital processing apparatus to undertake the present invention. This invention is realized in a critical machine component that causes a digital processing apparatus to perform the inventive method steps herein. The invention is also a computer-implemented method for  
20 undertaking the acts disclosed below.

Accordingly, a computer-implemented method for obtaining data from at least one user computer via the Internet while maintaining the privacy of a user of the computer includes perturbing original data associated with the user computer to render perturbed data. The method also includes generating at least one data mining model using the perturbed data.

5

In a preferred embodiment, perturbed data is generated from plural original data associated with respective plural user computers. As intended by the present invention, the original data cannot be reconstructed from the respective perturbed data. The data can be perturbed using a uniform probability distribution or a Gaussian probability distribution. Categorical data is perturbed by selectively replacing the data with other values based on a probability.

10

In another aspect, a computer system includes a program of instructions that include structure to, at a user computer, randomize at least some original values of at least some numeric attributes to render perturbed values. The program also sends the perturbed values to a server computer, where the perturbed values are processed to generate at least one classification model.

15

In still another aspect, a computer storage device includes computer readable code that is readable by a server computer for generating at least one classification model based on original data values stored at plural user computers without knowing the original values. The device includes logic means for receiving perturbed values from the user computers. In accordance with the present invention, the perturbed values represent randomized versions of the original values. Logic means then generate a classification model using the perturbed values without using the original values.

20

In yet another aspect, a computer storage device includes computer readable code readable by a user computer for facilitating the generation of at least one classification model based on

original data values stored at the user computer without knowing the original values. The device includes logic means for generating perturbed values representing randomized versions of the original values, and logic means for sending the perturbed values to a server computer for generating at least one classification model based thereon.

5           The details of the present invention, both as to its structure and operation, can best be understood in reference to the accompanying drawings, in which like reference numerals refer to like parts, and in which:

### **BRIEF DESCRIPTION OF THE DRAWINGS**

Figure 1 is a block diagram of the present system;

Figure 2 is a schematic diagram of a computer program product;

Figure 3 is a flow chart of the overall logic;

Figure 4 is a flow chart of the logic for reconstructing the data distribution of the original user data;

Figure 5 is a flow chart of the logic for generating a decision tree classifier; and

Figure 6 is a flow chart of the logic for generating a Naive Bayes classifier.

### **DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS**

Referring initially to Figure 1, a system is shown, generally designated 10, for mining data from plural user computers 12 (only a single user computer 12 shown in Figure 1 for clarity of disclosure) such that computer-implemented Web sites 14 can more effectively serve the user computers 12 while preserving the privacy of the user computers 12. The user computer 12

includes an input device 16, such as a keyboard or mouse, for inputting data to the computer 12, as well as an output device 18, such as a monitor, for displaying Web pages that have been tailored for the particular user of the computer 12. The Web pages are sent via the Internet from, e.g., the Web site 14.

5 One or both of the computer 12/Web site 14 can be a personal computer made by International Business Machines Corporation (IBM) of Armonk, N.Y. Other digital processors, however, may be used, such as a laptop computer, mainframe computer, palmtop computer, personal assistant, or any other suitable processing apparatus. Likewise, other input devices, including keypads, trackballs, and voice recognition devices can be used, as can other output  
10 devices, such as printers, other computers or data storage devices, and computer networks.

In any case, the processor of the user computer 12 accesses a perturbation module 20 to undertake certain of the logic of the present invention, while the Web site 14 accesses a privacy module 22 to undertake certain of the present logic. The modules 20, 22 may be executed by a processor as a series of computer-executable instructions. The instructions may be contained on a data storage device with a computer readable medium, such as a computer diskette 24 shown  
15 in Figure 2 having a computer usable medium 26 with code elements A-D stored thereon. Or, the instructions may be stored on random access memory (RAM) of the computers, on a DASD array, or on magnetic tape, conventional hard disk drive, electronic read-only memory, optical storage device, or other appropriate data storage device. In an illustrative embodiment of the  
20 invention, the computer-executable instructions may be lines of JAVA code.

Indeed, the flow charts herein illustrate the structure of the logic of the present invention as embodied in computer program software. Those skilled in the art will appreciate that the flow

charts illustrate the structures of computer program code elements including logic circuits on an integrated circuit, that function according to this invention. Manifestly, the invention is practiced in its essential embodiment by a machine component that renders the program code elements in a form that instructs a digital processing apparatus (that is, a computer) to perform a sequence of function steps corresponding to those shown.

Now referring to Figure 2, at block 28, the perturbation module 20 perturbs original data that the user of the user computer 12 wishes to remain private. For example, the user's age, income, and number of children might be perturbed at block 28. In one preferred embodiment, the data is perturbed using randomization.

For numerical attributes  $x_i$  such as age and salary, a perturbed value of  $x_i + r$  is returned, where  $r$  is a random value selected from a distribution. In one embodiment, the distribution is uniform, i.e.,  $r$  has a uniform probability distribution between  $[-\alpha, +\alpha]$  with a mean of 0. In another embodiment, the distribution is Gaussian, i.e.,  $r$  has a normal distribution with a mean " $\mu$ " of 0 and a standard deviation  $\sigma$ . In contrast, for categorical attributes such as profession, the true value of the attribute is returned with a probability  $p$ , with a value chosen at random from the other possible values for that attribute being returned with a probability of  $1-p$ .

Proceeding to block 30, in the preferred implementation the perturbed data is sent to the privacy module 22 at the Web site 14 via the Internet. Moving to block 32, the privacy module 22 builds a data mining model, also referred to herein as a classification model, based on the aggregated perturbed data from many users. The details of preferred methods for building the models, including reconstructing the distribution of the original data, are set forth further below. It is noted here, however, that although the preferred method includes reconstructing the

*distribution* of the original data from the distribution of the perturbed data, the Web site 14 does not know and cannot reconstruct original data, i.e., the attribute values of individual records from any user computer.

Once a data mining model is generated, several options are possible. For example, at block 34 the model can be sent as a JAVA applet to a user computer 12, which can then run the model at block 36 on its original records to determine a classification in accordance with the model. For example, the model might determine, based on the user's age and salary and assuming that the Web site is, e.g., the site of a vehicle vendor, that the user is of a classification that is inclined to purchase sports utility vehicles. The classification, but not the original data, can be returned to the Web site 14, which can then send a Web page that has been customized for the user's particular classification to the user computer 12 at block 38 for display of the page on, e.g., the monitor 18. Accordingly, the returned Web page might display and list SUVs more prominently than other vehicles, for the user's convenience, without compromising the privacy embedded in the original data, which is not available to the Web site 14.

Another option is shown at block 40 in Figure 3. If the user has generated a search request, the Web site 14 can return to the user the complete search results, along with a data mining model for ranking search results based on classification. The user computer 12 can then use the model to process its original data to return a classification, which is then used to rank the search results as a convenience for the user. Again, however, the user's original data remains unavailable to the Web site 14.

In the preferred embodiment, the data mining model is generated not from a distribution of the perturbed data, but from an estimate of the distribution of the original data that is



reconstructed from the distribution of the perturbed data, to improve the accuracy of the model. The estimate of the original distribution is referred to herein as the reconstructed distribution. Figure 4 shows the presently preferred method for generating the reconstructed distribution. As noted further below in reference to Figures 5 and 6, the algorithm shown in Figure 4 can be used prior to constructing the classification models or it can be integrated into the model generation process. Less preferably, in addition to or in lieu of generating the model, if desired the reconstructed data can be used for clustering or simply to gain an insight into the profile of the users of the system.

Commencing at block 42, a default uniform distribution is initially assumed, and at block 44 an integration cycle counter "j" is set equal to zero. Moving to block 46, the derivative of the posterior density function  $f_x^{j+1}$  can be determined for each attribute "a" using the following equation:

$$f_x^{j+1}(a) := (1/n) \sum (\text{over } i=1 \text{ to } n) \text{ of } \{ [f_y(w_i - a) f_x^j(a)] / \int (\text{from } -\infty \text{ to } +\infty) \text{ of } [f_y(w_i - z) f_x^j(z) dz] \}, \text{ where}$$

$f_x$  = derivative of the posterior distribution function for the reconstructed distribution,  $f_y$  = derivative of the posterior distribution function for the distribution of the perturbed data,  $n$  = number of independent random variables  $Y_1, Y_2, \dots, Y_n$ , with  $y_i$  being the realization of  $Y_i$ , it being understood that "Y" herein was referred to as "r" in the discussion of Figure 3,  $w_i = (x_i + y_i)$ ,  $a$  = attribute under test, and  $z$  is an integration variable satisfying, if  $Y$  is the standard normal,  $F_Y(z) = (1/((2\pi)^{.5}))e^{-(x^2x)/2}$ .

More preferably, to speed processing time, instead of determining the derivative of the posterior density function  $f_x^{j+1}$  at block 46, a partitioning of the domain of original data values for each attribute into "m" intervals "I" is assumed, and a probability  $\Pr(X \in I_p)$  that an original data point "X" lies within an interval  $I_p$  of the original distribution is found as follows. First, the

distance between  $z$  and  $w_i$  (or between  $a$  and  $w_i$ ) is approximated to be the distance between the midpoints of the intervals in which they lie. Also, the density function  $f_x(a)$  is approximated to be the average of the density function in the interval in which the attribute "a" lies.

With this in mind,

$$\Pr'(X \in I_p) = (1/n) \sum (\text{over } s=1 \text{ to } m) \text{ of } \{N(I_s) \times [(f_Y(m(I_s)) - m(I_p)) \Pr(X \in I_p)] / [\sum (\text{over } t=1 \text{ to } m) \text{ of } (f_Y(m(I_s)) - m(I_t)) \Pr(X \in I_t)]\}, \text{ where}$$

$I(x)$  is the interval in which "x" lies,  $m(I_p)$  is the midpoint of the interval  $I_p$ , and

$f(I_p)$  is the average value of the density function over the interval  $I_p$ ,  $p=1, \dots, m$ .

Using the preferred method of partitioning into intervals, the step at block 46 can be undertaken in  $O(m^2)$  time. It is noted that a naive implementation of the last of the above equations will lead to a processing time of  $O(m^3)$ ; however, because the denominator is independent of  $I_p$ , the results of that computation are reused to achieve  $O(m^2)$  time. In the presently preferred embodiment, the number "m" of intervals is selected such that there are an average of 100 data points in each interval, with "m" being bound  $10 \leq m \leq 100$ .

It is next determined at decision diamond 48 whether the stopping criterion for the iterative process disclosed above has been met. In one preferred embodiment, the iteration is stopped when the reconstructed distribution is statistically the same as the original distribution as indicated by a  $X^2$  goodness of fit test. However, since the true original distribution is not known, the observed randomized distribution (of the perturbed data) is compared with the is

compared with the result of the current estimation for the reconstructed distribution, and when the two are statistically the same, the stopping criterion has been met, on the intuition that if these two are close, the current estimation for the reconstructed distribution is also close to the original distribution.

5           When the test at decision diamond 48 is negative, the integration cycle counter "j" is incremented at block 50, and the process loops back to block 46. Otherwise, the process ends at block 52 by returning the reconstructed distribution.

Now referring to Figure 5, the logic for constructing a decision tree classifier using the reconstructed distribution is seen. Commencing at block 54, for each attribute in the set "S" of data points, a DO loop is entered. Moving to block 56, split points for partitioning the data set "S" pursuant to growing the data tree are evaluated. Preferably, the split points tested are those between intervals, with each candidate split point being tested using the so-called "gini" index set forth in Classification and Regression Trees, Breiman et al., Wadsworth, Belmont, 1984. To summarize, for a data set S containing "n" classes (which can be predefined by the user, if desired) the "gini" index is given by  $1 - \sum p_j^2$ , where  $p_j$  is the relative frequency of class "j" in the data set "S". For a split dividing "S" into subsets S1 and S2, the index of the split is given by:

$$\text{index} = n_1/n(\text{gini}(S1)) + n_2/n(\text{gini}(S2)), \text{ where } n_1 = \text{number of classes in } S1 \text{ and } n_2 = \text{number of classes in } S2.$$

The data points are associated with the intervals by sorting the values, and assigning the  $N(I_i)$  lowest values to the first interval, the next highest values to the next interval, and so on.

The split with the highest gini index is then used at block 58 to partition the data set into two subsets, with the lower intervals relative to the split point being in one subset and the higher intervals being in the other.

Proceeding to decision diamond 60, it is determined, for each partition, whether most elements in the partition are of the same class. If they are not, the logic proceeds to block 62 for each heterogenous partition to loop back to block 56 to further split that partition. Otherwise, when all partitions consist of elements most of which are of the same class, the logic prunes the tree at block 64 to remove dependence on statistical noise or variation that may be particular only to the training data, in accordance with decision tree prune principles set forth in, e.g., Minimum Description Length disclosed by Mehta et al. in "A Fast Scalable Classifier for Data Mining", Proc. of the Fifth Int'l Conf. on Extending Database Technology, Avignon, France (1996). The pruned tree is returned as the classifier. Thus, it is to be appreciated that since the preferred embodiment uses reconstructed data derived from the perturbed data, in a general sense the perturbed data is used to generate the classifier.

When using the logic of Figure 5, the reconstruction logic of Figure 4 can be invoked in one of three places. First, the reconstructed distribution can be generated for each attribute once prior to executing the logic of Figure 5 using the complete perturbed data set as the decision tree training set. The decision tree of Figure 5 is then induced using the reconstructed distribution.

Or, for each attribute, the training (perturbed) data can first be split by class, and then reconstructed distributions generated separately for each class, with the decision tree of Figure 5 being induced using the reconstructed distribution. Yet again, the by-class reconstruction need not be done once at the beginning, but rather at each node during the decision tree growth phase,

i.e., just before block 56 of Figure 5. We have found that the latter two methods very accurately track the original data and at the same time maintain the inability to know any particular original attribute value with any meaningful accuracy. For instance, in one experiment using a synthetic data generator and a training set of 100,000 records, the true age value for any particular original record could not be known, with 95% confidence, within an interval any smaller than 60 years. Nonetheless, the classifier generated by the above-disclosed reconstruction and decision tree logic very accurately resembled a similar classification model generated using the original data as a control. Moreover, we found that using a Gaussian randomizer at block 28 of Figure 3 resulted in even better privacy than using a uniform distribution randomizer, and that use of a Gaussian randomizer decreased the requirement for the reconstruction logic of Figure 4, although combining a Gaussian randomizer with reconstruction improved accuracy vis-a-vis generating a data mining decision tree model using uncorrected Gaussian-perturbed data.

Figure 6 shows that as an alternative to generating a decision tree classifier, a Naive Bayes classification model can be generated. Commencing at block 66, the classes  $c_j$  of data are determined empirically or using a decision tree-like growth phase such as the one shown in Figure 5, with the leaf nodes of the tree defining the classes. Moving to block 68, the probability  $\Pr(a_i = v_{ij} \mid C_j)$  of the  $i^{\text{th}}$  attribute "a" of a record having a value  $v_{ij}$  belonging to the  $j^{\text{th}}$  class is determined by determining the ratio of the number of records in the  $j^{\text{th}}$  class, divided by the total number of records, using the perturbed data as a training set.

Next, the logic determines proceeds to block 70, wherein the probability  $\Pr(r \mid C_j)$  of a record "r" given a class  $C_j$  is determined to be  $\prod (i=1 \text{ to } n) \text{ of } \Pr(a_i=v_i \mid C_j)$ , where  $a_i$  is an attribute that has the value  $v_i$ . As before, the preferred way to undertake the above calculation

is to partition the perturbed (training) data set into "m" intervals "I", and approximate  $\Pr(a_i=v_i | C_j)$  with  $\Pr(a_i \in P_i/C_j) = \frac{\text{number of records whose class is } C_j \text{ and } a_i \in P_i}{N(C_j)}$ , where the value of the attribute  $a_i$  is in the  $i^{\text{th}}$  interval partition. Mathematically, this is expressed as  $\{N(C_j \wedge a_i \in P_i)\}/N(C_j)$ . Also, the class probability  $\Pr(C_j)$  of a class occurring is determined using the training set.

After the step at block 70, at block 71 the probability  $\Pr(C_j | r)$  of a record  $r$  being in the class  $C_j$  is determined by combining the probability  $\Pr(r | C_j)$  with the class probability  $\Pr(C_j)$ . In a preferred embodiment, this is done by multiplying the value found at block 68 by the value determined at block 70 (i.e.,  $\{N(C_j \wedge a_i \in P_i)\}/N(C_j)$ ). The set of these probabilities for the various classes identified at block 66 is then returned at block 72 as the Naive Bayes classifier.

When using the logic of Figure 6, the reconstruction logic of Figure 4 can be invoked in one of two places. First, the reconstructed distribution can be generated for each attribute once prior to executing the logic of Figure 6 using the complete perturbed data set as the training set. The Naive Bayes classifier of Figure 6 is then induced using the reconstructed distribution. Or, for each attribute, the training (perturbed) data can first be split by class, and then reconstructed distributions generated separately for each class, i.e., after block 66.

While the particular SYSTEM AND ARCHITECTURE FOR PRIVACY-PRESERVING DATA MINING as herein shown and described in detail is fully capable of attaining the above-described objects of the invention, it is to be understood that it is the presently preferred embodiment of the present invention and is thus representative of the subject matter which is broadly contemplated by the present invention, that the scope of the present invention fully encompasses other embodiments which may become obvious to those skilled in the art, and that

the scope of the present invention is accordingly to be limited by nothing other than the appended claims, in which reference to an element in the singular is not intended to mean "one and only one" unless explicitly so stated, but rather "one or more". All structural and functional equivalents to the elements of the above-described preferred embodiment that are known or later come to be known to those of ordinary skill in the art are expressly incorporated herein by reference and are intended to be encompassed by the present claims. Moreover, it is not necessary for a device or method to address each and every problem sought to be solved by the present invention, for it to be encompassed by the present claims. Furthermore, no element, component, or method step in the present disclosure is intended to be dedicated to the public regardless of whether the element, component, or method step is explicitly recited in the claims. No claim element herein is to be construed under the provisions of 35 U.S.C. §112, sixth paragraph, unless the element is expressly recited using the phrase "means for" or, in the case of a method claim, the element is recited as a "step" instead of an "act".

WE CLAIM:

## CLAIMS

1           1.     A computer-implemented method for obtaining data from at least one user  
2 computer via the Internet while maintaining the privacy of a user of the computer, comprising  
3 the acts of:

4                     perturbing original data associated with the user computer to render perturbed data;

5                     and

6                     using the perturbed data, generating at least one data mining model.

1           2.     The method of Claim 1, wherein perturbed data is generated from plural original  
2 data associated with respective plural user computers.

1           3.     The method of Claim 2, wherein the original data cannot be reconstructed from  
2 the respective perturbed data.

1           4.     The method of Claim 2, wherein at least some of the data is perturbed using a  
2 uniform probability distribution.

1           5.     The method of Claim 2, wherein at least some of the data is perturbed using a  
2 Gaussian probability distribution.



1           6.     The method of Claim 2, wherein at least some of the data is perturbed by  
2 selectively replacing the data with other values based on a probability.

1           7.     A computer system including a program of instructions including structure to  
2 undertake method acts comprising:

3                 at a user computer, randomizing at least some original values of at least some  
4 numeric attributes to render perturbed values;

5                 sending the perturbed values to a server computer; and

6                 at the server computer, processing the perturbed values to generate at least one  
7 classification model.

8           8.     The computer of Claim 7, wherein perturbed values are generated from plural  
9 original values associated with respective plural user computers.

10          9.     The computer of Claim 7, wherein the original values cannot be reconstructed from  
11 the respective perturbed values.

1           10.    The computer of Claim 7, wherein at least some of the original values are  
2 perturbed using a uniform probability distribution.

1           11.    The computer of Claim 7, wherein at least some of the original values are  
2 perturbed using a Gaussian probability distribution.

1           12.     The computer of Claim 7, wherein the method acts further comprise perturbing  
2           categorical values of at least some categorical attributes by selectively replacing the categorical  
3           values with other values based on a probability.

1           13.     A computer storage device including computer readable code readable by a server  
2           computer for generating at least one classification model based on original data values stored at  
3           plural user computers without knowing the original values, comprising:

4                     logic means for receiving perturbed values from the user computers, the perturbed  
5                     values representing randomized versions of the original values; and

6                     logic means for generating at least one classification model using at least in part  
7                     the perturbed values and not using the original values.

1           14.     A computer storage device including computer readable code readable by a user  
2           computer for facilitating the generation of at least one classification model based on original data  
3           values stored at the user computer without knowing the original values, comprising:

4                     logic means for generating perturbed values representing randomized versions of  
5                     the original values; and

6                     logic means for sending the perturbed values to a server computer for generating  
7                     at least one classification model based thereon.

1           15.     The device of Claim 14, wherein the means for generating generates the perturbed  
2 values from original values.

1           16.     The device of Claim 14, wherein the original values cannot be reconstructed from  
2 the respective perturbed values.

1           17.     The device of Claim 14, wherein at least some of the original values are perturbed  
2 using a uniform probability distribution to render the perturbed values.

1           18.     The device of Claim 14, wherein at least some of the original values are perturbed  
2 using a Gaussian probability distribution to render the perturbed values.

1           19.     The device of Claim 14, wherein at least some of the original values are perturbed  
2 by selectively replacing the values with other values based on a probability.

1           20.     The method of Claim 1, further comprising sending the model to at least one user  
2 computer for use thereof by the user computer on original data.

1           21.     The method of Claim 20, wherein the user computer used the model on original  
2 data to render a classification, and then sends the classification to the Web site.

1                   22.     The method of Claim 20, wherein the model is sent to the user computer as a  
2     JAVA applet.

1                   23.     The system of Claim 7, wherein the method acts further comprise:  
2                   sending the model to at least one user computer for use thereof by the user  
3     computer on original data.

IBM Corp.  
Armonk, NY  
U.S.A.

## SYSTEM AND ARCHITECTURE FOR PRIVACY-PRESERVING DATA MINING

### ABSTRACT OF THE DISCLOSURE

5 A system and method for mining data while preserving a user's privacy includes perturbing user-related information at the user's computer and sending the perturbed data to a Web site. At the Web site, perturbed data from many users is aggregated, and from the distribution of the perturbed data, the distribution of the original data is reconstructed, although individual records cannot be reconstructed. Based on the reconstructed distribution, a decision tree classification model or a Naive Bayes classification model is developed, with the model then being provided back to the users, who can use the model on their individual data to generate classifications that are then sent back to the Web site such that the Web site can display a page appropriately configured for the user's classification. Or, the classification model need not be provided to users, but the Web site can use the model to, e.g., send search results and a ranking model to a user, with the ranking model being used at the user computer to rank the search results based on the user's individual classification data.





Fig 3 - overall flow




Fig 4- reconstructing original distribution





Fig. 5 Decision Tree classifier






Fig 6 Naive Bayes Classifier



**DECLARATION AND POWER OF ATTORNEY FOR PATENT APPLICATION**

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name.

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled

**SYSTEM AND ARCHITECTURE FOR PRIVACY-PRESERVING DATA MINING**

the specification of which is attached hereto unless the following box is checked:

was filed on \_\_\_\_\_

as United States Application Number or PCT International Application Number \_\_\_\_\_

and was amended on \_\_\_\_\_ (if applicable).

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose information which is material to patentability as defined in 37 CFR §1.56.

I hereby claim foreign priority benefits under 35 USC §119(a-d) or §365(b) of any foreign application(s) for patent or inventor's certificate, or §365(a) of any PCT International application which designated at least one country other than the United States, listed below and have also identified below, by checking the box, any foreign application for patent or inventor's certificate, or PCT International application having a filing date before that of the application on which priority is claimed.

**Prior Foreign Application(s):****Priority Not Claimed**

\_\_\_\_\_  
(Number) (Country) (Day/Month/Year Filed)

I hereby claim the benefit under 35 USC §119(e) of any United States provisional application(s) listed below:

**Provisional Application(s):**

\_\_\_\_\_  
(Application Number)

\_\_\_\_\_  
(Filing Date)

I hereby claim the benefit under 35 USC §120 of any United States application(s), or §365(c) of any PCT International application designating the United States, listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States or PCT International application in the manner provided by the first paragraph of 35 USC §112, I acknowledge the duty to disclose information which is material to patentability as defined in 37 CFR §1.56 which became available between the filing date of the prior application and the national or PCT International filing date of this application.

\_\_\_\_\_  
(Application Number) (Filing Date) (Status - patented, pending, abandoned)

**Power of Attorney:**

I hereby appoint the following attorney(s) and/or agent(s) to prosecute this application and to transact all business in the Patent and Trademark Office connected therewith:

Thomas R. Berthold	(#28,689)
Richard M. Ludwin	(#33,010)
Marc D. McSwain	(#44,929)
Khanh Q. Tran	(#41,352)
John L. Rogitz	(#33,549)
Alison D. Mortinger	(#39,306)

## Address all telephone calls to:

John L. Rogitz  
(619) 338-8075

## Address all correspondence to:


John L. Rogitz  
Rogitz & Associates  
750 B Street, Suite 3120  
San Diego, California 92101

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

## Full name of sole or first inventor:

RAKESH AGRAWAL

Inventor's signature:



Date: Jan 13, 2000

Residence:

1290 Quail Creek Circle, San Jose, California 95120

Citizenship:

United States

Post Office Address: Same


## Full name of second inventor: RAMAKRISHNAN SRIKANT

Inventor's signature:



Date: Jan 13, 2000

Residence:

~~4300 The Woods Drive #333, San Jose, California 95136~~  
1786 Magnolia Lake Ct. " " 95131 

Citizenship:

India

Post Office Address: Same